

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian
through T. 26 S.

CHAINS

17.96 Cougar Creek Trail, bears E. and W.

24.70 Creek, 1 lk. wide, course NW.

Ascend 344 ft. over broken SW. slope.

28.60 Enter burn, bears E. and W.

39.59 Intersect the old $\frac{1}{4}$ sec. cor., established for secs. 7
and 12, which is a basalt stone, 18x12x6 ins. above
ground, marked with a cross (X) at exact cor. point
and $\frac{1}{4}$ W. of cross.

I change this cor. to refer to sec. 12 only, obliterating
the marks on the old SE. bearing tree, from which

A fir stump, 8 ins. diam., bears S.61*E., 23 lks.

Marked $\frac{1}{4}$ S 7 B T (old B. T.)

A fallen fir, 7 ins. diam., bears S.80 $\frac{1}{2}$ *W., 17 lks.

Marked $\frac{1}{4}$ S 12 B T (old B. T.)

A fir, 6 ins. diam., bears S.45*W., 52 lks. dist.

Marked $\frac{1}{4}$ S 12 B T.

A fir, 6 ins. diam., bears N.25*W., 43 lks. dist.

Marked $\frac{1}{4}$ S 12 B T.

Thence,

N.0*21'E.,

7.36 Point for the $\frac{1}{4}$ sec. cor. of sec. 7, later determined.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in

ground, for the $\frac{1}{4}$ sec. cor. of sec. 7 only, with

brass cap marked,

|
| $\frac{1}{4}$ S 7
|
1928

from which

A fir, 20 ins. diam., bears N.60*E., 29 lks. dist.

Marked $\frac{1}{4}$ S 7 B T.

Raise a mound of stone, with a base 3 ft., 2 ft.

high E. of cor., as no other bearing tree was

available.