

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the Willamette Meridian  
through T. 26 S.

## CHAINS

15.00 Spur, slopes NW.

Descend 884 ft. over broken N. slope.

40.10 Intersect the old cor., established for secs. 1, 6, 7  
and 12, which is a basalt rock, 4x4x3 ft. marked  
with a cross (X) at exact cor. point, and 1 notch N.  
and 5 notches S. of cross.

I change this cor. to refer to secs. 1 and 12 only,  
obliterating the scribe marks on the NE. and SE.  
bearing trees, from which the original bearing trees

A fir snag, 24 ins. diam., bears N.25\*E., 34 lks.

Marked T 26 S R 1 E S 6 B T.

A fir snag, 24 ins. diam., bears S.54\*E., 53 lks.

Marked T 26 S R 1 E S 7 B T.

A cedar snag, 18 ins. diam., bears S.88\*W., 59 lks.

Marked T 26 S R 1 W S 12 B T.

A hemlock snag, 18 ins. diam., bears N.30\*W., 74 lks.

Marked T 26 S R 1 W S 1 B T.

Land, mountainous.

Soil, stony, third rate.

Timber, fir, hemlock and cedar.

Undergrowth, vine maple and arrowwood.

N.0\*45\*W., resurveying the E. bdy. of sec. 1.

Descend 452 ft. over broken N. slope, through timber  
and brush.

.40 Creek, 1 lk. wide, course N.30\*E.

7.36 Point for the closing cor. of secs. 6 and 7, later  
determined and hereinafter described.

18.20 Creek, 6 lks. wide, course NW, enter timber and brush  
bears E. and W.

Ascend 228 ft. over broken SW. slope.

40.19 Intersect the old  $\frac{1}{2}$  sec. cor., established for secs. 1  
and 6, which is a basalt stone, 8x6x4 ins. above  
ground, marked  $\frac{1}{2}$  on W. face.