


County Surveyor's Record, Douglas County, Oregon

Survey of the E. Bdy. of T. 26 S., R. 1 E.

CHAINS



from which

A fir, 4 ins. diam., bears N.37*E., 19 lks. dist.

Marked T 26 S R 2 E S 7 B T.

A fir, 8 ins. diam., bears S.35*E., 19 lks. dist.

Marked T 26 S R 2 E S 18 B T.

A fir, 20 ins. diam., bears S.49*W., 57 lks. dist.

Marked T 26 S R 1 E S 13 B T.

A fir, 18 ins. diam., bears N.80*W., 52 lks. dist.

Marked T 26 S R 1 E S 12 B T.

Land, mountainous.

Soil, rocky and loam, third rate.

Timber, fir and hemlock.

Undergrowth, greasewood and vine maple.


North, bet. secs. 7 and 12.

Descend 30 ft. over N. slope, through timber and brush.

9.20 Creek, 3 lks. wide, course SE.

Ascend 541 ft. over broken S. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the 1/4 sec. cor., with brass cap marked,



from which

A fir, 4 ins. diam., bears S.63*E., 17 lks. dist.

Marked 1/4 S 7 B T.

A fir, 10 ins. diam., bears N.78*W., 41 lks. dist.

Marked 1/4 S 12 B T.

Ascend 450 ft. over SE. slope.

56.50 Top of bluff, 100 ft. high, faces S., bears E. and W.