

County Surveyor's Record, Douglas County, Oregon


Survey of the E. Bdy. of T. 26 S., R. 1 E.

CHAINS

56.60 Spur, slopes E.  
Descend 57 ft. over N. slope.

67.50 Ravine, course E.  
Ascend 156 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in ground, for the cor. of secs. 1, 6, 7 and 12, with brass cap marked,



from which

- A fir, 4 ins. diam., bears N.54\*E., 27 lks. dist.  
Marked T 26 S R 2 E S 6 B T.
- A fir, 16 ins. diam., bears S.30\*E., 56 lks. dist.  
Marked T 26 S R 2 E S 7 B T.
- A fir, 12 ins. diam., bears S.67\*W., 51 lks. dist.  
Marked T 26 S R 1 E S 12 B T.
- A fir, 4 ins. diam., bears N.83\*W., 18 lks. dist.  
Marked T 26 S R 1 E S 1 B T.

Land, mountainous.  
Soil, rocky and loam, third rate.  
Timber, fir and hemlock.  
Undergrowth, vine maple and rhododendron.

North, bet. secs. 1 and 6.  
Descend 50 ft. over broken NE. slope, through timber and brush.

8.90 Draw, course SE.  
Ascend 135 ft. over broken SE. slope.

21.10 Divide bet. Steamboat Creek and the North Umpqua River, bears E. and W.  
Descend 185 ft. over broken NE. slope.

28.40 Draw, course NE.