


County Surveyor's Record, Douglas County, Oregon

Survey of the N. Bdy. of T. 26 S., R. 21 E.

CHAINS

70:30 Creek, 3 lks. wide, course NE.
Ascend 99 ft. over E. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in ground, for the cor. of secs. 1, 2, 35 and 36, with brass cap marked,



from which

A fir, 7 ins. diam., bears N.58*E., 47 lks. dist.

Marked T 25 $\frac{1}{2}$ S R 1 E S 36 B T.

A fir, 7 ins. diam., bears S.9*E., 14 lks. dist.

Marked T 26 S R 1 E S 1 B T.

A fir, 12 ins. diam., bears S.21*W., 32 lks. dist.

Marked T 26 S R 1 E S 2 B T.

A fir, 8 ins. diam., bears N.77*W., 27 lks. dist.

Marked T 25 $\frac{1}{2}$ S R 1 E S 35 B T.

Land, mountainous.

Soil, rocky and loam, third rate.

Timber, fir, hemlock and cedar and pine.

Undergrowth, rhododendron, salal and second growth timber.

West, bet. secs. 2 and 35.

Ascend 94 ft. over NE. slope, through timber and brush.

5.00 Spur, slopes N.30*E.

Descend 32 ft. over NW. slope.

12.20 Spring branch, 1 lks. wide, course N.

Ascend 361 ft. over broken NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

