

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

from which

A fir, 14 ins. diam., bears N.25*E., 28 lks. dist.

Marked T 26 S R 1 E S 25 B T.

A fir, 24 ins. diam., bears S.64*E., 26 lks. dist.

Marked T 26 S R 1 E S 36 B T.

A fir, 18 ins. diam., bears S.47*W., 27 lks. dist.

Marked T 26 S R 1 E S 35 B T.

A fir, 15 ins. diam., bears N.77*W., 46 lks. dist.

Marked T 26 S R 1 E S 26 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir, pine and madrone.

Undergrowth, rhododendron and vine maple.

East, on a random line bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.70 Intersect the E. Bdy. of the Tp., 12 lks. N. of the cor.
of secs. 25, 30, 31 and 36, hereinbefore described.

Thence,

N.89*55*W., on a true line bet. secs. 25 and 36.

Over mountainous land, through timber and brush.

Ascend 466 ft. over broken SE. slope.

1.00 Spring branch, 1 lk. wide, course SE.

11.90 Point of spur, slopes S.

Descend 175 ft. over broken SW. slope.

21.00 Creek, 1 lk. wide, course SE. Asc. 468 ft. over E. slope.

37.80 Same creek, 1 lk. wide, course N.80*E.

39.85 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

S25
 $\frac{1}{4}$ ———
S36

1928

from which