

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS	
	<p>A fir, 10 ins. diam., bears S.61*W., 92 lks. dist.                      Marked T 26 S R 1 E S 23 B T.                      A fir, 20 ins. diam., bears N.12*W., 145 lks. dist.                      Marked T 26 S R 1 E S 14 B T.</p> <p>Land, mountainous.                      Soil, rocky loam, third rate.                      Timber, fir and madrone.                      Undergrowth, vine maple and rhododendron.</p>
	<p>S.89*58'E., on a random line bet. secs. 13 and 24.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.78	Intersect the E. bdy. of the Tp., 2 lks. S. of the cor. of sec. 13, 18, 19 and 24, hereinbefore described.
	Thence, N.89*59'W., on a true line bet. secs. 13 and 24.
	Descend 30 ft. over SW. slope, through timber and brush.
1.40	Creek, 1 lk. wide, course S.
	Ascend 190 ft. over E. slope.
19.00	Spur slopes S.
	Descend 86 ft. over SW. slope.
28.50	Draw, course S.
	Ascend 100 ft. over SE. slope.
37.30	Spur, slopes S.
39.89	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,
	$\begin{array}{r} S13 \\ \frac{1}{4} \text{---} \\ S24 \\ 1928 \end{array}$
	from which
	A fir, 6 ins. diam., bears S.3*W., 94 lks. dist. Marked $\frac{1}{4}$ S 24 B T.
	A fir, 4 ins. diam., bears N.2*W., 260 lks. dist. Marked $\frac{1}{4}$ S 13 B T.
	Descend 330 ft. over steep SW. slope.