

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

the ground, for the cor. of secs. 11, 12, 13 and 14,  
with brass cap marked,

T26SR1E	
S11	S12
S14	S13
1928	

from which

A fir, 10 ins. diam., bears N.54\*E., 98 lks. dist.

Marked T 26 S R 1 E S 12 B T.

A fir, 24 ins. diam., bears S.32\*E., 183 lks. dist.

Marked T 26 S R 1 E S 13 B T.

A fir, 18 ins. diam., bears S.63\*W., 286 lks. dist.

Marked T 26 S R 1 E S 14 B T.

A fir, 18 ins. diam., bears N.39\*W., 79 lks. dist.

Marked T 26 S R 1 E S 11 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir.

Undergrowth, scrub oak, greasewood, vine maple and choke  
cherry.

S.89\*59'E., on a random line bet. secs. 12 and 13.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.94 Intersect the E. bdy. of the Tp., 23 lks. S. of the cor.  
of secs. 7, 12, 13 and 18., hereinbefore described.

Thence,

S.89\*51'W., on a true line bet. secs. 12 and 13.

Ascend 401 ft. over E. slope, through timber and brush.

14.00 Spur, slopes SE.

Descend 165 ft. over SW. slope.

30.10 Draw, course S.20\*E.

Ascend 70 ft. over SE. slope.

39.97 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked,