

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

39.00 Draw, course SW.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the 1/4 sec. cor., with brass cap marked,



from which

A fir, 8 ins. diam., bears S.29*E., 58 lks. dist.

Marked 1/4 S 12 B T.

A fir, 10 ins. diam., bears N.35*W., 15 lks. dist.

Marked 1/4 S 11 B T.

Ascend 23 ft. over SW. slope.

41.50 Spur, slopes SW.

Descend 23 ft. over NW. slope.

43.40 Creek, 1 lk. wide, course SW.

Ascend 625 ft. over broken SW. slope.


45.00 Small spur, slopes SW.

46.40 Spring branch, 1 lk. wide, course S.30*W.

75.50 Spur, slopes W.

Descend 220 ft. over N. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 1, 2, 11 and 12, with brass cap marked,



from which

A fir, 12 ins. diam., bears N.35*E., 44 lks. dist.

Marked T 26 S R 1 E S 1 B T.

A fir, 12 ins. diam., bears S.39*E., 60 lks. dist.

Marked T 26 S R 1 E S 12 B T.

A fir, 16 ins. diam., bears S.62*W., 30 lks. dist.

Marked T 26 S R 1 E S 11 B T.

A fir, 12 ins. diam., bears N.27*W., 37 lks. dist.

Marked T 26 S R 1 E S 2 B T.