

Subdivisions, T. 26 S., R. 1 E.

CHAINS

Soil, rocky loam, third rate.

Timber, fir.

Undergrowth, vine maple, rhododendron and service berry.

N.0\*01'W., on a random line bet. secs. 1 and 2.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.80.20 Intersect the N. bdy. of the Tp., 14 lks. E. of the cor.  
of secs. 1, 2, 35 and 36, hereinbefore described.

Thence,

S.0\*07'E., on a true line bet. secs. 1 and 2.

Ascend 490 ft. over broken N. slope, through timber and  
brush.

9.30 Spring branch, 1 lk. wide, course NE.

32.30 Divide, bet. the N. Umpqua river and Steamboat Creek,  
bears E. and W.

Descend 123 ft. over SW. slope.

40.20 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked,
$$\begin{array}{c} \frac{1}{4} \\ | \\ S\ 2\ | \ S\ 1 \\ | \\ 1928 \end{array}$$

from which

A fir, 10 ins. diam., bears S.51\*E., 28 lks. dist.

Marked  $\frac{1}{4}$  S 1 B T.

A fir, 10 ins. diam., bears S.66\*W., 27 lks. dist.

Marked  $\frac{1}{4}$  S 2 B T.

Descend 89 ft. over SW. slope.

44.90 Creek, 1 lk. wide, course S.75\*W.

Ascend 120 ft. over NW. slope.

50.40 Spur, slopes W.

Descend 209 ft. over SW. slope.

61.10 Dry creek bed, 2 lks. wide, course W.

Ascend 500 ft. over broken NW. slope.