

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

- 51.20 Draw, course N.15\*E.
- 60.10 Spring branch, 1 lk. wide, course N.10\*E.
- 66.60 Same creek, 1 lk. wide, course N.30\*W.
- Thence over broken land.
- 75.90 Draw, course W.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground to bedrock, supported by a mound of stone with a 4 ft. base, 1 ft. high, for the cor. of secs. 26, 27, 34 and 35, with brass cap marked,

T26SR1E	
S27	S26
S34	S35

1928

from which

- A fir, 40 ins. diam., bears N.23\*E., 27 lks. dist.  
Marked T 26 S R 1 E S 26 B T.
- A fir, 30 ins. diam., bears S.26\*E., 8 lks. dist.  
Marked T 26 S R 1 E S 35 B T.
- A fir, 30 ins. diam., bears S.44\*W., 83 lks. dist.  
Marked T 26 S R 1 E S 34 B T.
- A fir, 30 ins. diam., bears N.42\*W., 56 lks. dist.  
Marked T 26 S R 1 E S 27 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir.

Undergrowth, rhododendron and vine maple.

East, on a random line, bet. secs. 26 and 35.

- 40.00 Set temp.  $\frac{1}{2}$  sec. cor.
- 80.32 Intersect the N. and S. line, 23 lks. S. of the cor. of secs. 25, 26, 35 and 36.
- Thence,  
S.89\*50'W., on a true line bet. secs. 26 and 35  
Over broken N. slope, through timber and brush.