

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T: 26 S., R. 1 E.

CHAINS


N.0*02'W., bet. secs. 26 and 27.

Over mountainous land, through timber and brush.

Descend 1050 ft. over broken NW. slope.

32.10 Draw, course NW.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,



from which

A fir, 18 ins. diam., bears S.79*E., 33 lks. dist.

Marked $\frac{1}{4}$ S 26 B T.

A fir, 12 ins. diam., bears S.65*W., 31 lks. dist.

Marked $\frac{1}{4}$ S 27 B T.

Descend 330 ft. over NW. slope.

48.70 West Limpy Creek, 10 lks. wide, course NE.


Ascend 300 ft. over SE. slope.

65.10 Spur, slopes E.

Descend 550 ft. over NE. slope.

67.20 Series of rocky bluffs, facing the NE.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 22, 23, 26 and 27, with brass cap marked,



from which

A hemlock, 14 ins. diam., bears N.13*E., 87 lks.

Marked T 26 S R 1 E S 23 B T.

An alder, 8 ins. diam., bears S.43*E., 26 lks. dist.

Marked T 26 S R 1 E S 26 B T.

A fir, 60 ins. diam., bears S.42*W., 78 lks. dist.

Marked T 26 S R 1 E S 27 B T.

A hemlock, 10 ins. diam., bears N.54*W., 23 lks. dist.

Marked T 26 S R 1 E S 22 B T.