

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 10, 11, 14 and 15, with brass cap marked,

T26SR1E
 $\frac{S10}{S15} | \frac{S11}{S14}$
 1928

from which

A fir, 8 ins. diam., bears N.20*E., 78 lks. dist.

Marked T 26 S R 1 E S 11 B T.

A fir, 16 ins. diam., bears S.49*E., 58 lks. dist.

Marked T 26 S R 1 E S 14 B T.

A fir, 8 ins. diam., bears S.43*W., 35 lks. dist.

Marked T 26 S R 1 E S 15 B T.

A fir, 18 ins. diam., bears N.32*W., 48 lks. dist.

Marked T 26 S R 1 E S 10 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir, pine and madrone.

Undergrowth, vine maple and second growth timber.

N.89*59*E., on a random line bet. secs. 11 and 14.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.08 Intersect the N. and S. line, 12 lks. N. of the cor. of secs. 11, 12, 13 and 14.

Thence,

N.89*56*W., on a true line bet. secs. 11 and 14.

Over mountainous land, through timber and brush.

Descend 1155 ft. over broken SW. slope

11.70 Spur, slopes S.80*W.

14.71 Jackass Mountain Trail, bears N. and S.

40.04 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

S11
 $\frac{1}{4}$
 S14
 1928