

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

from which

A fir, 5 ins. diam., bears N.24\*E., 14 lks. dist.

Marked  $\frac{1}{4}$  S 11 B T.

A fir, 12 ins. diam., bears S.33\*W., 15 lks. dist.

Marked  $\frac{1}{4}$  S 14 B T.

Descend 520 ft. over W. slope.

51.20 Apple Creek, 1 lk. wide, course SW.

Ascend 360 ft. over SE. slope.

68.40 Spur, slopes SW.

Descend 500 ft. over SW. slope.

80.08 The cor. of secs. 10, 11, 14 and 15.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir and madrone.

Undergrowth, greasewood and vine maple.

N.0\*02'W., bet. secs. 10 and 11.

Ascend 745 ft. over broken SW. slope, through timber and brush.

2.00 Draw, course W.

6.30 Small spur, slopes SW.

10.30 Draw, course SW.

14.50 Top of bluff, 125 ft. high, bears E. and W., faces S.

20.70 Spur, slopes SW.

26.60 Draw, course SW.

30.06 Jackass Mountain Trail, bears E. and W.

30.50 Spur, slopes W.

Descend 414 ft. over NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked,
$$\begin{array}{c} \frac{1}{4} \\ | \\ S10 | S11 \\ | \\ 1928 \end{array}$$