

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS	
	<p>from which</p> <p>A fir, 16 ins. diam., bears S.87*E., 48 lks. dist. Marked $\frac{1}{2}$ S 11 B T.</p> <p>A fir, 12 ins. diam., bears S.84*W., 76 lks. dist. Marked $\frac{1}{2}$ S 10 B T.</p> <p>Descend 210 ft. over NW. slope.</p>
45.60	<p>Creek, 1 lk. wide, course W.</p> <p>Ascend 212 ft. over SW. slope.</p>
49.10	<p>Point of a spur, slopes SW.</p>
55.00	<p>Draw, course S.70*W.</p>
56.00	<p>Spur, slopes SW.</p> <p>Descend 303 ft. over NW. slope.</p>
67.90	<p>Creek, 1 lk. wide, course N.75*W.</p> <p>Ascend 130 ft. over SW. slope.</p>
72.00	<p>Spur, slopes W.</p> <p>Descend 104 ft. over NW. slope.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 2, 3, 10 and 11, with brass cap marked,</p>
	<p>T26SR1E S 3 S 2 S10 S11 1928</p>
	<p>from which</p> <p>A fir, 24 ins. diam., bears N.22*E., 77 lks. dist. Marked T 26 S R 1 E S 2 B T.</p> <p>A fir, 36 ins. diam., bears S.40*E., 16 lks. dist. Marked T 26 S R 1 E S 11 B T.</p> <p>A yew, 6 ins. diam., bears S.83*W., 46 lks. dist. Marked T 26 S R 1 E S 10 B T.</p> <p>A fir, 9 ins. diam., bears N.55*E., 34 lks. dist. Marked T 26 S R 1 E S 3 B T.</p> <p>Land, mountainous.</p> <p>Soil, rocky loam, third rate.</p>