

## Subdivisions, T. 26 S., R. 1 E.

## CHAINS

79.60 Intersect the N. and S. line, 5 lks. N. of the cor. of  
secs. 22, 23, 26 and 27.

Thence,

N.89°57'W., on a true line bet. secs. 22 and 27.

Ascend 617 ft. over broken NE. slope, through timber  
and brush.

17.20 Spur, slopes N.

Descend 64 ft. over NW. slope.

23.00 Draw, course N.

Ascend 530 ft. over broken NE. slope.

24.70 Top of rock bluff, 70 ft. high, bears N. and S., faces E.

38.00 Spur, slopes N.

Descend 60 ft. over NW. slope.

39.80 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked,

$$\begin{array}{r} S22 \\ \frac{1}{4} \\ \hline S27 \\ 1928 \end{array}$$

from which

A fir, 24 ins. diam., bears N.61°E., 82 lks. dist.

Marked  $\frac{1}{4}$  S 22 B T.

A fir, 26 ins. diam., bears S.72°E., 54 lks. dist.

Marked  $\frac{1}{4}$  S 27 B T.

Descend 350 ft. over NW. slope.

51.00 Draw, course N.

Ascend 190 ft. over NE. slope.

56.20 Spur, slopes N.

Descend 310 ft. over NW. slope.

63.70 Creek, 1 lk. wide, course N.

Ascend 220 ft. over NE. slope.

71.00 Spur, slopes N.

Descend 114 ft. over NW. slope.