

Subdivisions, T. 26 S., R. 1 E.

CHAINS

Ascend 219 ft. over SW. slope.

71.60 Spur, slopes SE.

Descend 35 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 15, 16, 21 and 22, with brass cap marked,

| | |
|---------|-----|
| T26SR1E | |
| S16 | S15 |
| S21 | S22 |
| 1928 | |

from which

A fir, 10 ins. diam., bears N.54*E., 193 lks. dist.

Marked T 26 S R 1 E S 15 B T.

A fir, 7 ins. diam., bears S.16*E., 91 lks. dist.

Marked T 26 S R 1 E S 22 B T.

A fir, 10 ins. diam., bears S.44*W., 137 lks. dist.

Marked T 26 S R 1 E S 21 B T.

A fir, 30 ins. diam., bears N.64*W., 52 lks. dist.

Marked T 26 S R 1 E S 16 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir and cedar.

Undergrowth, vine maple and second growth timber.

S.89*57'E., on a random line bet. secs. 15 and 22.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.00 Intersect the N. and S. line, 33 lks. N. of the cor. of secs. 14, 15, 22 and 23.

Thence,

N.89*43'W., on a true line bet. secs. 15 and 22.

Over mountainous land, through timber and brush.

Descend 452 ft. over W. slope.

10.30 Limpy Creek, 10 lks. wide, course N.15*W.

Ascend 241 ft. over E. slope.

23.40 Spur, slopes N.65*E.