

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS	
	<p>from which</p> <p>A cedar, 16 ins. diam., bears N.36*E., 125 lks. dist. Marked T 26 S R 1 E S 10 B T.</p> <p>A fir, 8 ins. diam., bears S.50*E., 133 lks. dist. Marked T 26 S R 1 E S 15 B T.</p> <p>A fir, 10 ins. diam., bears S.71*W., 85 lks. dist. Marked T 26 S R 1 E S 16 B T.</p> <p>A fir, 8 ins. diam., bears N.53*W., 137 lks. dist. Marked T 26 S R 1 E S 9 B T.</p> <p>Land, mountainous. Soil, rocky loam, third rate. Timber, fir, cedar and madrone. Undergrowth, vine maple.</p>
	<p>S.89*43'E., on a random line bet. secs. 10 and 15.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.88	Intersect the N. and S. line, 44 lks. S. of the cor. of secs. 10, 11, 14 and 15.
	Thence,
	S.89*58'W., on a true line bet. secs. 10 and 15. Over mountainous land, through timber and brush. Descend 800 ft. over broken SW. slope.
4.20	Draw, course SW.
15.80	Draw, course S.30*W.
21.70	North Umpqua Trail and telephone line, bears S.45*E. and N.75*W.
35.00	North Umpqua River, 180 lks. wide, course NW. Ascend 130 ft. over NE. slope.
39.94	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,
	$\begin{array}{r} S10 \\ \frac{1}{4} \\ \hline S15 \\ 1928 \end{array}$