

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

$$\begin{array}{c} \frac{1}{2} \\ | \\ \text{S } 9 \mid \text{S } 10 \\ | \\ 1928 \end{array}$$

from which

A yew, 5 ins. diam., bears S.88*E., 55 lks. dist.

Marked $\frac{1}{2}$ S 10 B T.

A pine, 8 ins. diam., bears N.83*W., 46 lks. dist.

Marked $\frac{1}{2}$ S 9 B T.

A boulder in place, 18x24x30 ins. above ground bears

N.25*E., marked with a cross (X).

Descend 270 ft. over broken NE. slope.

42.00 Spur, slopes NE.

51.68 Creek, 10 lks. wide, course E.

Ascend 108 ft. over SE. slope.

55.20 Spur, slopes E.

Descend 194 ft. over NE. slope.

63.40 South end of cable bridge, bears E. 80 lks.

65.00 North Umpqua River, 180 lks. wide, course NW.

68.84 North Umpqua River Trail and telephone line, bears SE.
and NW.Ascend 314 ft. over broken bluffs and scattering timber
on SW. slope.80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in
the ground, for the cor. of secs. 3, 4, 9 and 10, with
brass cap marked,
$$\begin{array}{c} \text{T26SR1E} \\ \hline \text{S } 4 \mid \text{S } 3 \\ \hline \text{S } 9 \mid \text{S } 10 \\ \hline 1928 \end{array}$$

from which

A fir, 36 ins. diam., bears N.62*E., 100 lks. dist.

Marked T 26 S R 1 E S 3 B T.

A madrone, 9 ins. diam., bears S.17*E., 75 lks. dist.

Marked T 26 S R 1 E S 10 B T.

A fir, 14 ins. diam., bears S.45*W., 26 lks. dist.

Marked T 26 S R 1 E S 9 B T.