

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

Descend 660 ft. over broken N. slope.

40.60 Spring branch, 1 lk. wide, course N.75*E.

41.10 Creek, 3 lks. wide, course S.75*E.

54.20 Small draw, course E.

55.27 North and South Trail and telephone line, bears SE. and NW.

61.10 Spur, slopes N.80*E.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 28, 29, 32 and 33, with brass cap marked,

T26SR1E	
S29	S28
S32	S33
1928	

from which

A fir, 42 ins. diam., bears N.60*E., 142 lks. dist.

Marked T 26 S R 1 E S 28 B T.

A fir, 12 ins. diam., bears S.26*E., 90 lks. dist.

Marked T 26 S R 1 E S 33 B T.

A hemlock, 30 ins. diam., bears S.26*W., 124 lks.

Marked T 26 S R 1 E S 32 B T.

A fir, 48 ins. diam., bears N.52*W., 100 lks. dist.

Marked T 26 S R 1 E S 29 B T.

Land, mountainous.

Soil, rocky, third rate.

Timber, fir, hemlock and cedar.

Undergrowth, vine maple, rhododendron and second growth timber.

East, on a random line bet. secs. 28 and 33.

40.00 Set temp. 1/4 sec. cor.

79.58 Intersect the N. and S. line, 35 lks. N. of the cor. of secs. 27, 28, 33 and 34.

Thence,

N.89*45*W., on a true line bet. secs. 28 and 33.