

## County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

## CHAINS

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 20, 21, 28 and 29, with brass cap marked,

T26SR1E	
S20	S21
S29	S28
1928	

from which

A cedar, 36 ins. diam., bears N.38\*E., 68 lks. dist.

Marked T 26 S R 1 E S 21 B T.

A cedar, 28 ins. diam., bears S.42\*E., 54 lks. dist.

Marked T 26 S R 1 E S 28 B T.

A fir, 20 ins. diam., bears S.18\*W., 66 lks. dist.

Marked T 26 S R 1 E S 29 B T.

A fir, 20 ins. diam., bears N.32\*W., 43 lks. dist.

Marked T 26 S R 1 E S 20 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir and cedar.

Undergrowth, vine maple and second growth timber.

S.89\*45'E., on a random line bet. secs. 21 and 28.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.98 Intersect the N. and S. line, 5 lks. N. of the cor. of secs. 21, 22, 27 and 28.

Thence;

N.89\*43'W., on a true line bet. secs. 21 and 28.

Descend 150 ft. over W. slope, through timber and brush.

5.50 Creek, 1 lk. wide, course N.15\*W.

Ascend 180 ft. over NE. slope.

10.80 Spur, slopes N.

Descend 210 ft. over NW. slope.

29.70 Creek, 3 lks. wide, course NE.

Ascend 125 ft. over E. slope.