

Subdivisions, T. 26 S., R. 1 E.

CHAINS	
35.40	Spur, slopes NE. Descend 120 ft. over NW. slope.
39.99	Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked, <div style="text-align: center;"> $\frac{S21}{\frac{1}{4}}$ $S28$ 1928 </div> from which A cedar, 14 ins. diam., bears N.11*E., 18 lks. dist. Marked $\frac{1}{4}$ S 21 B T. A hamlock, 14 ins. diam., bears S.21*W., 71 lks. dist. Marked $\frac{1}{4}$ S 28 B T.
40.60	Dry creek bed, course N.10*E. Ascend 790 ft. over broken E. slope.
70.15	North and South Trail and telephone line, bears NE. and SW.
75.90	Ridge, bears N.25*E., and S.25*W. Descend 67 ft. over NW. slope.
79.98	The cor. of secs. 20, 21, 28 and 29. Land, mountainous. Soil, rocky, third rate. Timber, fir, hemlock and cedar. Undergrowth, second growth timber.
	N.0*03*W., bet. secs. 20 and 21. Descend 590 ft. over broken NW. slope, through timber and brush.
18.50	Panther creek, 5 lks. wide, course N.55*E. Ascend 80 ft. over SE. slope.
27.00	Spur, slopes NE. Descend 25 ft. over N. slope.
31.00	Creek, 1 lk. wide, course SE. Ascend 70 ft. over SE. slope.
38.70	Spur, slopes SE.