

Subdivisions, T. 26 S., R. 1 E.

CHAINS

N.0*03*W., bet. secs. 16 and 17.

Ascend 114 ft. over broken S. slope, through timber and brush.

3.40 Spur, slopes S.80*E.

4.30 Spring branch, 1 lk. wide, course SE.

9.30 Spur, slopes S.60*E.

Descend 25 ft. over NE. slope.

14.00 Draw, course S.60*E.

Ascend 62 ft. over S. slope.

17.60 Spur, slopes SE.

Descend 20 ft. over NE. slope.


21.50 Draw, course S.20*E.

Ascend 348 ft. over broken S. slope.

26.50 Point of a spur, slopes S.30*E.

28.00 Draw, course S.30*E.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,



from which

A fir, 8 ins. diam., bears S.31*E., 125 lks. dist.

Marked $\frac{1}{4}$ S 16 B T.

A madrone, 4 ins. diam., bears N.66*W., 40 lks.

Marked $\frac{1}{4}$ S 17 B T.

Ascend 290 ft. over broken S. slope.

55.31 Cougar Creek Trail, bears E. and W.

55.40 Ridge, divide bet. Panther Creek and the North Umpqua River, bears E. and W.

Descend 500 ft. over broken N. slope.

73.00 Creek, 2 lks. wide, course NE.

Ascend 95 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 8, 9, 16 and 17, with brass cap marked,