

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

T26SR1E  
S 8 | S 9  
S17 | S16  
1928

from which

A pine, 16 ins. diam., bears N.42\*E., 142 lks. dist.

Marked T 26 S R 1 E S 9 B T.

A hemlock, 30 ins. diam., bears S.46\*E., 86 lks.

Marked T 26 S R 1 E S 16 B T.

A fir, 12 ins. diam., bears S.45\*W., 26 lks. dist.

Marked T 26 S R 1 E S 17 B T.

A hemlock, 12 ins. diam., bears N.25\*W., 77 lks.

Marked T 26 S R 1 E S 8 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir and madrone.

Undergrowth, chinquapin, cinnamon bark and second growth timber.

S.89\*56'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. 1/4 sec. cor.

79.96 Intersect the N. and S. line, 16 lks. S. of the cor. of secs. 9, 10, 15 and 16.

Thence,

S.89\*57'W., on a true line bet. secs. 9 and 16.

Over mountainous land, through timber and brush.

Ascend 570 ft. over broken E. slope.

9.80 Spur, slopes N.80\*E.

33.10 Spur, slopes N.

Descend 178 ft. over NW. slope.

39.70 Creek, 1 lk. wide, course N.25\*E.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the 1/4 sec. cor., with brass cap marked,