

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

West, on a true line bet. secs. 30 and 31.
 Ascend 168 ft. over NE. slope, through timber and brush.
 14.40 Spur, slopes N.
 Descend 140 ft. over broken NW. slope.
 19.20 Creek, 2 lks. wide, course NW., thence over N. slope.
 24.70 Draw, course N.
 31.80 Draw, course N.15*E.
 Ascend 40 ft. over NE. slope.
 35.90 Spur, slopes N.
 Descend 130 ft. over NW. slope.
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
 the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

S30
 $\frac{1}{4}$ ———
 S31
 1928

from which
 A hemlock, 24 ins. diam., bears N.11*E., 40 lks.
 Marked $\frac{1}{4}$ S 30 B T.
 A fir, 40 ins. diam., bears S.63*W., 143 lks. dist.
 Marked $\frac{1}{4}$ S 31 B T.
 This cor. is set at the base of a bluff, 15 ft. high,
 bears NE. and SW., faces NW.

40.70 Branch Creek, 4 lks. wide, course N.20*E.
 Ascend 140 ft; over E. slope.
 46.90 Draw, course SE., descend 14 ft. over NW. slope.
 51.20 Draw, course N., ascend 76 ft. over E. slope.
 54.90 Spur, slopes N.65*E.
 Ascend 70 ft. over NE. slope.
 59.95 Cougar Creek Trail, bears N. and S.
 63.00 Spur, slopes N.15*W.
 Descend 110 ft. over NW. slope.
 73.60 Dry creek bed, 2 lks. wide, course NW.
 Ascend 80 ft. over NE. slope.
 78.40 Intersect the Willamette Meridian, 5.10 chs. N.0*23'E.
 of the cor. of secs. 25 and 36 only, hereinbefore described.