

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.


CHAINS

West, on a true line bet. secs. 19 and 30.

Over mountainous land, through timber and brush.

Ascend 460 ft. over broken E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,



from which

A fir, 20 ins. diam., bears S.70*E., 48 lks. dist.

Marked $\frac{1}{4}$ S 30 B T.

A fir, 16 ins. diam., bears N.20*W., 5 lks. dist.

Marked $\frac{1}{4}$ S 19 B T.

Ascend 210 ft. over E. slope.

52.98 Cougar Creek Trail, bears N.10*E., and S.10*W.

55.80 Ridge, bears N. and S.


Descend 210 ft. over broken W. slope.

73.40 Creek, 2 lks. wide, course N.30*W.

77.40 Intersect the Willamette Meridian, 6.44 chs. N.0*26'E., of the cor. of secs. 24 and 25 only, as hereinbefore described.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 19 and 30, with brass cap marked,



from which

A fir, 14 ins. diam., bears N.45*E., 87 lks. dist.

Marked T 26 S R 1 E S 19 C C B T.

A fir, 12 ins. diam., bears S.48*E., 53 lks. dist.

Marked T 26 S R 1 E S 30 C C B T.