

## Subdivisions, T. 26 S., R. 1 E.

## CHAINS

Descend 230 ft. over NE. slope.

70.60 Creek, 2 lk. wide, course SE.

75.10 Creek, 1 lk. wide, course SE.

Ascend 70 ft. over S. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 17, 18, 19 and 20, with brass cap marked,

T26SR1E	
S18	S17
S19	S20
1928	

from which

A fir, 6 ins. diam., bears N.71\*E., 45 lks. dist.

Marked T 26 S R 1 E S 17 B T.

A fir, 16 ins. diam., bears S.15\*E., 117 lks. dist.

Marked T 26 S R 1 E S 20 B T.

A fir, 10 ins. diam., bears S.39\*W., 79 lks. dist.

Marked T 26 S R 1 E S 19 B T.

A fir, 7 ins. diam., bears N.30\*W., 30 lks. dist.

Marked T 26 S R 1 E S 18 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir, hemlock, pine and cedar.

Undergrowth, vine maple.

S.89\*48'E., on a random line bet. secs. 17 and 20.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.60 Intersect the N. and S. line, 40 lks. S. of the cor. of secs. 16, 17, 20 and 21.

Thence,

S.89\*55'W., on a true line bet. secs. 17 and 20.

Ascend 450 ft. over broken E. slope, through timber and brush.