

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

	S18
$\frac{1}{4}$	—
	S19
	1928

from which

A fir, 12 ins. diam., bears N.56*E., 33 lks. dist.

Marked $\frac{1}{4}$ S 18 B T.

A fir, 12 ins. diam., bears S.26*W., 14 lks. dist.

Marked $\frac{1}{4}$ S 19 B T.

Descend 1534 ft. over broken W. slope.

66.50 Spring branch, 1 lk. wide, course N.60*E.

76.10 Intersect the Willamette Meridian, 5.35 chs. N.2*13'E.,
of the cor. of secs. 13 and 24 only, hereinbefore described.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in
the ground, for the closing cor. of secs. 18 and 19,
with brass cap marked,

T26S		T26S
		S18
S13		— CC
		S19
RLW		RLB
		1928

from which

A fir, 20 ins. diam., bears N.70*E., 85 lks. dist.

Marked T 26 S R 1 E S 18 C C B T.

A fir, 26 ins. diam., bears S.75*E., 24 lks. dist.

Marked T 26 S R 1 E S 19 C C B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir, pine and madrone.

Undergrowth, vine maple.

From the cor. of secs. 17, 18, 19 and 20.

Thence,

N.0*04*W., bet. secs. 17 and 18.

Ascend 140 ft. over SE. slope, through timber and brush.