

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

A fir, 14 ins. diam., bears S.24*W., 70 lks. dist.

Marked T 26 S R 1 E S 18 B T.

A fir, 6 ins. diam., bears N.62*W., 56 lks. dist.

Marked T 26 S R 1 E S 7 B T.

Land, mountainous.

Soil, rocky, third rate.

Timber, fir, hemlock and cedar.

Undergrowth, vine maple.

N.89*55'E., on a random line bet. secs. 8 and 17.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.70 Intersect the N. and S. line, 21 lks. S. of the cor. of
secs. 8, 9, 16 and 17.

Thence,

S.89*46*W., on a true line bet. secs. 8 and 17.

Descend 44 ft. over gradual W. slope, through timber
and brush.

5.70 Creek, 1 lk. wide, course N.60*E., from the W.

Ascend 460 ft. over broken E. slope.

17.00 Leave same creek, course E., from the SW.

39.85 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in
the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

$$\begin{array}{r} S 8 \\ \frac{1}{4} \\ \hline S 17 \\ 1928 \end{array}$$

from which

A fir, 6 ins. diam., bears S.28*W., 44 lks. dist.

Marked $\frac{1}{4}$ S 17 B T.

A fir, 12 ins. diam., bears N.3*W., 95 lks. dist.

Marked $\frac{1}{4}$ S 8 B T.

SE. cor. of Winslow's cabin bears N.65*W., 210 lks.
dist.