

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

Descend 230 ft. over slide rock on NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap marked,

$$\begin{array}{c} \frac{1}{4} \\ \uparrow \\ \text{S } 7 \mid \text{S } 8 \\ \downarrow \\ 1928 \end{array}$$

from which

The SW. face of an outcrop, 8x8 ft., bears N.40*E., 100 lks. dist., marked with a cross X at true point and $\frac{1}{4}$ S 8 B 0.

A boulder, 6x6x4 ft. above ground, bears N.74*W., 52 lks. dist., marked with a cross (X) at true point and $\frac{1}{4}$ S 7 B 0.

Descend 415 ft. over NW. slope.

49.70 Draw, course W.

Ascend 180 ft. over broken rough SW. slope.

61.40 Spur, slopes NW.

Descend 520 ft. over broken N. slope.

78.50 Draw, course N.25*W.

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the cor. of secs. 5, 6, 7 and 8, with brass cap marked,

$$\begin{array}{c} \text{T26SR1E} \\ \text{S } 6 \mid \text{S } 5 \\ \text{S } 7 \mid \text{S } 8 \\ 1928 \end{array}$$

from which

A madrone, 5 ins. diam., bears N.65*E., 123 lks. dist.

Marked T 26 S R 1 E S 5 B T.

A maple, 4 ins. diam., bears S.20*E., 14 lks. dist.

Marked T 26 S R 1 E S 8 B T.

A fir, 20 ins. diam., bears S.61*W., 194 lks. dist.

Marked T 26 S R 1 E S 7 B T.