

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

A fir, 15 ins. diam., bears N.74\*W., 190 lks. dist.

Marked T 26 S R 1 E S 6 B T.

Land, mountainous.

Soil, rocky loam, third rate.

Timber, fir, cedar and madrone.

Undergrowth, vine maple, greasewood and manzanita.

N.89\*46'E., on a random line bet. secs. 5 and 8.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

79.68 Intersect the N. and S. line, 23 lks. N. of the cor. of  
secs. 4, 5, 8 and 9.

Thence,

S.89\*56'W., on a true line bet. secs. 5 and 8.

Over mountainous land, through timber and brush.

Ascend 350 ft. over broken NE. slope.

28.70 Draw, course N.

31.70 Small spur, slopes N.

Descend 41 ft. over NW. slope.

38.70 Draw, course N.

Ascend 32 ft. over NE. slope.

39.84 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in  
the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap marked,

S 5  
 $\frac{1}{4}$  ———  
S 8  
1928

from which

A fir, 9 ins. diam., bears S.74\*W., 51 lks. dist.

Marked  $\frac{1}{4}$  S 8 B T.

A fir, 16 ins. diam., bears N.47\*W., 68 lks. dist.

Marked  $\frac{1}{4}$  S 5 B T.

Ascend 60 ft. over NE. slope.

44.90 Spur, slopes N.