

County Surveyor's Record, Douglas County, Oregon

Subdivisions, T. 26 S., R. 1 E.

CHAINS

Ascend 170 ft. over E. slope.

68.30 Spur, slopes N.

Descend 80 ft. over W. slope.

70.60 Creek, 1 lk. wide, course N.30*E.

Ascend 70 ft. over NE. slope.

72.94 Intersect the Willamette Meridian, 7.36 chs. N.0*45*W., of the cor. of secs. 1 and 12 only, hereinbefore described.

At point of intersection;

Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground, for the closing cor. of secs. 6 and 7, with brass cap marked,

T26S	T26S
S 1	S 6
	CC
	S 7
R1W	R1E
	1928

from which

A fir, 36 ins. diam., bears N.20*E., 58 lks. dist.

Marked T 26 S R 1 E S 6 C C B T.

A fir, 40 ins. diam., bears S.18*E., 90 lks. dist.

Marked T 26 S R 1 E S 7 C C B T.

Land, mountainous.

Soil, rocky, third rate.

Timber, fir.

Undergrowth, vine maple, greasewood, cinnamon bark and dog wood.

From the cor. of secs. 5, 6, 7 and 8.

Thence,

N.0*04*W., on a random line bet. secs. 5 and 6.

40.00 Set temp. 1/2 sec. cor.

80.40 Intersect the N. bdy. of the Tp., 30 lks. E. of the cor. of secs. 5, 6, 31 and 32, hereinbefore described.

Thence,