

County Surveyor's Record, Douglas County, Oregon


East and North Boundaries and Subdivisions of T. 26 S., R. 2 E., as surveyed by Otto S. Draper, U. S. Transitman, under Special Instructions dated Dec. 24, 1920.

E. Bdy. of T. 26 S., R. 2 E.

CHAINS

From the cor. of Tps. 26 and 27 S., Rs. 2 and 3 E., as described in the field notes of T. 27 S., R. 2 E. North, on E. bdy. of Tp., bet. secs. 31 and 36. Desc. 243 ft. over broken NW. slope, through heavy timber and medium undergrowth.

- 19.00 Creek, 2 lks. wide, course W.,
- 22.90 Copeland Creek, 20 lks. wide, course NE., desc. 16 ft. along broken NE. slope.
- 30.00 Copeland Creek, 20 lks. wide, at bend, course NE., from SE., asc. 30 ft. along SE. slope.
- 33.90 Spur, slopes E., desc. 32 ft. over NE. slope.
- 36.70 Copeland Creek, course NW., asc. 24 ft. over SW. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 31 and 36, with brass cap marked



from which,

- A fir, 14 ins. diam., bears N.18*E., 15 lks. dist., mkd. $\frac{1}{4}$ S 31 B T
- A fir, 34 ins. diam., bears N.44*W., 25 lks. dist., mkd. $\frac{1}{4}$ S 36 B T

Asc. 170 ft. over SW. slope.

- 53.70 Spur, slopes W., desc. 80 ft. over NW. slope.
- 56.20 Draw, course W., asc. 208 ft. over broken SW. slope.
- 74.00 Top of bluff, 145 ft. high, bears N. and SE., thence along face of bluffs.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., over cross (X) marked on solid rock, in mound of stone, 6 ft. base, 3 ft. high, for cor. of secs. 25, 30, 31 and 36, with brass cap marked



1929

from which,