

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 26 S., R. 2 E.

CHAINS

A fir, 8 ins. diam., bears S.73\*W., 35 lks.

dist., mkd. ¼ S 12 B T

Asc. 145 ft. over SE. slope.

56.50 Spur, slopes SE., desc. 60 ft. over N. slope.

59.30 Draw, course E., asc. 440 ft. over broken SE. slope.

79.80 Spur, slopes E., desc. 3 ft. over NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 1, 6, 7, and 12, with brass cap mkd.

T26S	
R2E	R3E
S 1	S 6
S12	S 7

1930

from which,

A fir, 40 ins. diam., bears N.22\*E., 63 lks.

dist., mkd. T 26 S R 3 E S 6 B T

A fir, 20 ins. diam., bears S.29\*E., 46 lks.

dist., mkd. T 26 S R 3 E S 7 B T

A fir, 30 ins. diam., bears S.39\*W., 57 lks.

dist., mkd. T 26 S R 2 E S 12 B T

A fir, 36 ins. diam., bears N.34\*W., 55 lks.

dist., mkd. T 26 S R 2 E S 1 B T

Land; mountainous.

Soil; S. ½ mile, rocky, 4th rate; N. ½ mile, mountain loam, 3rd rate.

Timber; fir, pine, cedar, hemlock, and madrona.

Undergrowth; vinemaple, hazel, chinquapin, dog-wood, and small fir.

North bet. secs. 1 and 6

Desc. 550 ft. over NE. slope, through medium timber and dense undergrowth.

22.20 Creek, 6 lks. wide, course E., asc. 250 ft. over broken SW. slope.