

North Boundary of T. 26 S., R. 2 E.

CHAINS

N.89*52'W., on true line bet. secs. 3 and 34

Asc. 230 ft. over E. slope, through medium timber and dense undergrowth.

5.50 Spur, slopes SE., asc. 100 ft. over SE. slope.

12.10 Draw, course SE., asc. 610 ft. over E. slope.

22.00 Telephone line bears NE. and SW.

25.70 Ridge, bears NE. and SW., desc. 580 ft. over NW. slope.

30.60 Grassy Ranch Trail, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 3 and 34, with brass cap mkd.

$\frac{1}{4}$ $\frac{S34}{S 3}$
1930

from which,

A fir, 14 ins. diam., bears N.34*E., 5 lks.

dist., mkd. $\frac{1}{4}$ S 34 B T

A fir, 16 ins. diam., bears S.44*W., 24 lks.

dist., mkd. $\frac{1}{4}$ S 3 B T

Desc. 120 ft. over NW. slope.

42.50 Draw, course NW., asc. 110 ft. over NE. slope.

52.00 Spur, slopes N.; desc. 190 ft. over broken NW. slope.

67.40 Draw, course NW., asc. 240 ft. over NE. slope.

76.20 Spur, slopes NW., desc. 100 ft. over SW. slope.

80.00 Point for cor. falls on face of steep sloping rock, impracticable to set cor.

At point 42 lks. S. of true cor. point, set an iron post, 3 ft. long, 2 ins. diam., 18 ins. in the ground, to bed rock, and in mound of stone, 3 ft. base, for witness cor. to the cor. of secs. 3, 4, 33 and 34, with brass cap mkd.

W C
T25 $\frac{1}{2}$ S | R2E
S33 | S34

S 4 | S 3
T26S
1930