

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of Tp. described in the field notes of T. 27 S., R. 2E. N.0°01'W., bet. secs. 35 and 36.

Desc. 119 ft. over N. slope, through heavy timber and medium undergrowth.

8.60 Desc. 100 ft. over broken NE. slope.

11.90 Draw, course NE.,

16.00 Creek, 2 lks. wide, course SE. for 1.50 chs. thence NE., asc. 224 ft. over SW. slope.

23.70 Spur, slopes N.70°E., desc. 260 ft. over NE. slope.

34.20 Creek, 2 lks. wide, course SE., asc. 134 ft. over SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of secs. 35 and 36, with brass cap mkd.



from which,

A fir, 16 ins. diam., bears N.88°E., 45 lks. dist., mkd.  $\frac{1}{4}$  S 36 B T

A yew, 4 ins. diam., bears S.45°W., 13 lks. dist., mkd.  $\frac{1}{4}$  S 35 B T

Asc. 50 ft. over SE. slope,

43.90 Spur, slopes SE., desc. 75 ft. over NE. slope.

52.80 Creek, 1 lk. wide, course SE., asc. 348 ft. over SW. slope.

69.50 Spur, slopes SE., desc. 70 ft. over gradual NE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

