

Subdivisions of T.26 S., R. 2 E.

CHAINS	
	S.89*58'E., on a random line bet. secs. 24 and 25.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.48	Intersect E. bdy. of Tp. 30 lks. S. of cor. of secs. 19, 24, 25, and 30, hereinbefore described.
	Thence
	S.89*49'W., on true line bet. secs. 24 and 25
	Along gradual S. slope, through heavy timber and medium undergrowth.
18.00	Desc. 76 ft. over gradual SW. slope.
25.90	Bottom of descent bears NW. and SE., thence over nearly level land, Oak Flats.
32.70	North Umpqua Trail, and telephone line, bears NW. and SE.
40.24	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bed rock, and in mound of stone, 3 ft. base, for $\frac{1}{4}$ sec. cor. of secs. 24 and 25, with brass cap mkd.
	$\frac{1}{4}$ $\frac{S24}{S25}$
	1929
	from which,
	A fir, 18 ins. diam., bears S.30*E., 141 lks. dist., mkd. $\frac{1}{4}$ S 25 B T
	An oak, 6 ins. diam., bears N.44*W., 23 lks. dist., mkd. $\frac{1}{4}$ S 24 B T
	Over flat.
46.40	Top of rim, 180 ft. high, bears NW. and SE., desc. 680 ft. over SW. slope; dist. measured with a 5-chain steel tape, compared with a Lufkin Standard 1-chain steel tape, and found correct.
67.20	Copeland Creek, 35 lks. wide, course NW., asc. 182 ft. over broken NE. slope, to cor.
71.40	Spur, slopes NE.,
74.90	Draw, course N.,