

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS	
40.00	<p>Set an iron post, 3 ft. long, 1 in. diam., 16 ins. in the ground, to bed rock, and in a mound of stone, 3 ft. base, for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, with brass cap mkd.</p>
	$\begin{array}{c} \frac{1}{4} \\ \\ \text{S14} \text{S13} \\ \\ 1929 \end{array}$
	<p>from which,</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S.58*E., 83 lks. dist., mkd. $\frac{1}{4}$ S 13 B T</p> <p style="padding-left: 40px;">A pine, 36 ins. diam., bears S.44*W., 374 lks. dist., mkd. $\frac{1}{4}$ S 14 B T</p>
	<p>Asc. 90 ft. over steep S. slope.</p>
43.00	<p>Top of Cliff, bears N.2*W., and SE., desc. 240 ft. along E. face of cliff.</p>
50.30	<p>Foot of cliff, bears S.2*E., and NW., desc. 120 ft. over NE. slope, through heavy timber and medium undergrowth.</p>
59.60	<p>Draw, course SE., asc. 430 ft. over S., changing to precipitous SW. slope.</p>
66.50	<p>Top of rock, 180 ft. high at W. end; 300 ft. high at E. end; bears W. 75 lks. and E. about 3.00 chs., Spur, slopes S.75*E., desc. 490 ft. over precipitous N., changing to broken NE. slope.</p>
74.00	<p>Outcrop of rock, 100x40x80 ft. above ground, bears E. and W.,</p>
77.30	<p>Draw, course E., asc. 60 ft. over SE. slope.</p>
80.00	<p>Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 11, 12, 13, and 14, with brass cap mkd.</p>
	$\begin{array}{c} \text{T26S} \text{R2E} \\ \text{S11} \text{S12} \\ \hline \text{S14} \text{S13} \\ 1930 \end{array}$