

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

40.22 Set an iron post, 3 ft. long, 1 in. diam., 17 ins. in the ground, to bed rock, and in mound of stone, 2½ ft. base, for ¼ sec. cor. of secs. 1 and 2, with brass cap mkd.



from which,

A fir, 8 ins. diam., bears S.70\*E., 24 lks.  
dist., mkd. ¼ S 1 B T

A fir, 8 ins. diam., bears N.62\*W., 8 lks.  
dist., mkd. ¼ S 2 B T

Desc. 50 ft. over SE. slope.

42.90 Creek, 2 lks. wide, course SW., asc. 98 ft. over broken NW. slope.


51.40 Spur, slopes W., desc. 425 ft. over SW. slope.

69.20 Creek, 10 lks. wide, course SE., asc. 240 ft. over NE. slope.

71.00 Spring, course NE.

77.20 Point of spur; slopes E., desc. 91 ft. over SE. slope.

79.89 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for witness cor. to the cor. of secs. 1, 2, 11 and 12, with brass cap mkd.



from which,

A fir, 12 ins. diam., bears N.40\*E., 59 lks.  
dist., mkd. W C T 26 S R 2 E S 1 B T

A hemlock, 20 ins. diam., bears S.9\*E., 75 lks.  
dist., mkd. W C T 26 S R 2 E S 12 B T

A hemlock, 10 ins. diam., bears S.31\*W., 83 lks.  
dist., mkd. W C T 26 S R 2 E S 11 B T