

Subdivisions of T. 26 S., R. 2 E.

CHAINS

N.0*02'W., bet. secs. 26 and 27.

Desc. 4 ft. over N. slope, through heavy timber and medium undergrowth.

0.20 Draw, course NW., desc. 67 ft. along W. slope.

15.10 Spur, slopes NW., desc. 495 ft. over NE. slope.

31.60 Creek, 1 lk. wide, course NW., desc. 40 ft. over NW. slope.

36.70 Wilson Creek, 1 lk. wide, course NE., desc. 30 ft. along NE. slope.

40.00 A fir, 20 ins. diam., for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27; I mark,

$\frac{1}{4}$ S 27 on W.,
and S 26 on E., sides.

from which,

A fir, 18 ins. diam., bears N.79*E., 84 lks.
dist., mkd. $\frac{1}{4}$ S 26 B T

A cedar, 17 ins. diam., bears S.72*W., 58 lks.
dist., mkd. $\frac{1}{4}$ S 27 B T

Desc. 30 ft. along broken E. slope.

52.70 Draw, course E1,

60.50 Desc. 170 ft. over broken NE. slope.

73.40 Creek, 1 lk. wide, course NE., desc. 87 ft. over NE. slope.

76.20 Hole-in-the-Ground Trail, bears NW. and SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, to bed rock, and in mound of stone, 5 ft. base, for cor. of secs. 22, 23, 26, and 27, with brass cap mkd.

T26S	R2E
S22	S23
S27	S26

1929

from which,

A fir, 20 ins. diam., bears N.57*E., 26 lks.
dist., mkd. T 26 S R 2 E S 23 B T

A fir, 44 ins. diam., bears S.45*E., 101 lks.
dist., mkd. T 26 S R 2 E S 26 B T