

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS	
	<p>A yew, 10 ins. diam., bears S.33*W., 50 lks. dist., mkd. T 26 S R 2 E S 27 B T</p> <p>A fir, 30 ins. diam., bears N.47*W., 25 lks. dist., mkd. T 26 S R 2 E S 22 B T</p> <p>Land; mountainous.</p> <p>Soil; mountain loam, rocky, 3rd and 4th rates.</p> <p>Timber; fir, cedar, hemlock, pine, and yew.</p> <p>Undergrowth; vinemaple, rhododendron, and arrow-wood.</p>
	<p>N.89*47'E. on a random line bet. secs. 23 and 26</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.90	Intersect N. and S. line 16 lks. S. of cor. of secs. 23, 24, 25 and 26, hereinbefore described
	Thence
	S.89*40'W. on true line bet. secs. 23 and 26.
	Asc. 132 ft. over NE. slope, through heavy timber and medium undergrowth.
5.30	Spur, slopes N., desc. 100 ft. over NW. slope.
9.90	Draw, course N., asc. 641 ft. over broken NE. slope.
11.20	Draw, course NE.,
12.90	Twin Lakes Trail bears NE. and SW.,
15.30	Same trail, bears N. and S.,
16.80	Same trail, bears N. and SW.,
18.30	Same trail, bears SW. and SE.,
19.30	Same trail, bears SE. and NW.,
23.70	Same trail, bears NE. and SW.,
24.90	Same trail, bears SE. and NW.,
25.70	Same trail, bears NE. and NW.,
32.20	Spur, slopes NW., desc. 112 ft. over NW. slope.
34.12	Intersect line bet. corners Nos. 3 and 4, H. E. S. No. 229; cor. No. 3 bears N.65*12'E., 4.82 chs. dist.
39.95	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 23 and 26, with brass cap mkd.