

Subdivisions of T. 26 S., R. 2 E.

CHAINS	Thence	West	30 lks. to
31.70	Point on true line, asc. 240 ft. over SW. slope.		
40.00	Point for $\frac{1}{4}$ sec. cor. falls on face of bluff 70 ft. high impracticable to set cor., asc. 30 ft. over SW. slope.		
41.30	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for witness cor. to $\frac{1}{4}$ sec. cor. of secs. 14 and 15, with brass cap mkd.		
	$\begin{array}{c} \frac{1}{4} \\   \\ S15   S14 \\   \\ W   C \\ 1929 \end{array}$		
	from which,		
	A fir, 6 ins. diam., bears S.65*E., 29 lks. dist., mkd. W C $\frac{1}{4}$ S 14 B T		
	A pine, 18 ins. diam., bears N.32*W., 25 lks. dist., mkd. W C $\frac{1}{4}$ S 15 B T		
	Cor. on top of high peak on Eagle ridge, desc. 200 ft. over N. slope, along top of spur,		
54.80	Spur, slopes N.10*E., desc. 620 ft. over broken NE. slope, through heavy timber and medium undergrowth.		
73.20	Draw, course NE.,		
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10, 11, 14 and 15, with brass cap mkd.		
	$\begin{array}{c} T26S   R2E \\ S10   S11 \\ \hline S15   S14 \\ 1929 \end{array}$		
	from which,		
	A fir, 10 ins. diam., bears N.52*E., 45 lks. dist., mkd. T 26 S R 2 E S 11 B T		
	A fir, 10 ins. diam., bears S.42*E., 22 lks. dist., mkd. T 26 S R 2 E S 14 B T		
	A fir, 11 ins. diam., bears S.62*W., 30 lks. dist., mkd. T 26 S R 2 E S 15 B T		