

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 26 S., R. 2 E.

CHAINS	
	<p>A fir, 11 ins. diam., bears N.4*W., 33 lks. dist., mkd. T 26 S R 2 E S 10 B T</p> <p>Land; rough mountainous. Soil; rocky, 4th rate. Timber; fir, pine, and cedar. Undergrowth; buck brush, vinemaple, hazel, small fir, and arrow-wood.</p>
	<p>N.89*47'E., on a random line bet. secs. 11 and 14.</p>
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.30	Intersect N. and S. line 5 lks. N. of cor. of secs. 11, 12, 13, and 14, hereinbefore described
	Thence
	S.89*49'W., on true line bet. secs. 11 and 14.
	Asc. 745 ft. over broken SE. slope, over bluffs, through heavy timber and medium undergrowth.
21.30	Rattlesnake Ridge, bears NW. and SE., desc. 212 ft. over SW. slope, through very scattering timber.
30.10	Draw, course SW., asc. 48 ft. along SE. slope.
37.00	Spur, slopes S.20*W., desc. 78 ft. over SW. slope.
40.15	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 11 and 14, with brass cap mkd.
	$\frac{1}{4} \frac{S11}{S14}$
	1929
	from which,
	A fir, 5 ins. diam., bears S.53*E., 73 lks. dist., mkd. $\frac{1}{4}$ S 14 B T
	A fir, 4 ins. diam., bears N.78*W., 154 lks. dist., mkd. $\frac{1}{4}$ S 11 B T
	Along S. slope.
44.30	Desc. 359 ft. over SW. slope.