

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 21, 22, 27 and 28, with brass cap mkd.

T26S	R2E
S21	S22
S28	S27

1929

from which,

A pine, 8 ins. diam., bears $N.44^{\circ}E.$, 37 lks.

dist., mkd. T 26 S R 2 E S 22 B T

A fir, 36 ins. diam., bears $S.39^{\circ}E.$, 57 lks.

dist., mkd. T 26 S R 2 E S 27 B T

A pine, 14 ins. diam., bears $S.24^{\circ}W.$, 70 lks.

dist., mkd. T 26 S R 2 E S 28 B T

A pine, 54 ins. diam., bears $N.63^{\circ}W.$, 15 lks.

dist., mkd. T 26 S R 2 E S 21 B T

Land; mountainous.

Soil; mountain loam, 3rd rate.

Timber; fir, pine, hemlock, yew and cedar.

Undergrowth; rhododendron, vinemaple, and hazel.

S.89*55'E., on random line bet. secs. 22 and 27

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.34 Intersect N. and S. line, 16 lks. S. of cor. of secs. 22, 23, 26 and 27, hereinbefore described.

Thence

S.89*58'W., on true line bet. secs. 22 and 27

Asc. 80 ft. over NE. slope, through medium timber and medium undergrowth.

3.80 Spur, slopes NW., desc. 275 ft. over NW. slope.

5.80 Hole-in-the-Ground Trail, bears NW. and SE.,

9.30 Same trail bears NE. and SW.

15.50 Creek, 1 lk. wide, course N., asc. 41 ft. over gradual