

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

40.18 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, with brass cap mkd.

$\frac{1}{4}$   $\frac{S10}{S15}$

1929

from which,

A fir, 26 ins. diam., bears South, 74 lks. dist.,  
mkd.  $\frac{1}{4}$  S 15 B T

A fir, 24 ins. diam., bears N.29\*W., 6 lks. dist.,  
mkd.  $\frac{1}{4}$  S 10 B T

Asc. 278 ft. over SE. slope.

48.40 Grassy Ranch Trail, bears NE. and SW.

60.40 Spur, slopes S., desc. 102 ft. over SW. slope.

69.00 Draw, course S., asc. 124 ft. over SE. slope.

74.80 Spur, ridge, bears NE. and SW., desc. 175 ft. over NW. slope.

80.36 Cor. of secs. 9, 10, 15 and 16.

Land; mountainous.

Soil; rocky, 4th rate.

Timber; fir, pine, hemlock, and madrona.

Undergrowth; vinemaple, mountain laurel, greasewood,  
arrow-wood, dogwood, willow and hazel.

N.0\*02'W., bet. secs. 9 and 10.

Desc. 612 ft. over broken NW. slope, to  $\frac{1}{4}$  sec. cor.,  
through heavy timber and medium undergrowth.

14.00 Spur, slopes W.,

15.00 Draw, course W.,

19.50 Spur, slopes W.,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, with brass cap mkd.