

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS	
	N.89*53'E., on a random line bet. secs. 28 and 33
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.88	Intersect N. and S. line, 19 lks. N. of cor. of secs. 27, 28, 33, and 34, hereinbefore described.
	Thence
	N.89*59'W., on true line bet. secs. 28 and 33.
	Desc. 570 ft. over SW. slope, through heavy timber and dense undergrowth.
15.00	Top of bluff, 150 ft. high, bears N. and SE.
16.40	Creek, 1 lk. wide, course NW., asc. 209 ft. over broken gradual NE. slope.
21.60	Low spur, slopes NE.,
23.60	Draw, course N.60*E.,
35.50	Spur, slopes NE., desc. 148 ft. over NW. slope.
39.94	Set a basalt stone, 7x14x26 ins., 20 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, marked, a cross (X) on top at the exact cor. point and $\frac{1}{4}$ on N. face.
	from which,
	A fir, 24 ins. diam., bears N.11*E., 86 lks. dist., mkd. $\frac{1}{4}$ S 28 B T
	A fir, 40 ins. diam., bears S.38*E., 37 lks. dist., mkd. $\frac{1}{4}$ S 33 B T
	Desc. 210 ft. over NW. slope.
45.60	Deception Creek, 4 lks. wide, course N.15*E., asc. 483 ft. over E., changing to NE. slope.
66.10	Spur, slopes NE., desc. 14 ft. over NW. slope.
68.40	Creek, 1 lk. wide, course NE., asc. 180 ft. over NE., changing to E. slope.
75.90	Hole-in-the-Ground Trail, bears NE. and SW.
79.88	Cor. of secs. 28, 29, 32 and 33.
	Land; mountainous.
	Soil; rocky, mountain loam, 4th rate.
	Timber; fir, cedar, hemlock, yew, and madrona.