

66

Subdivisions of T. 26 S., R. 2 E.

CHAINS

- 43.60 Spur, slopes NE.,
- 43.63 Set a basalt stone, 7x14x27 ins., 22 ins. in the ground, for witness cor. to the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, mkd., a cross (X) on top at exact cor. point, and W C $\frac{1}{4}$ on N. face.
- from which,
- A fir, 12 ins. diam., bears N.35*E., 15 lks. dist., mkd. W C $\frac{1}{4}$ S 21 B T
- A fir, 13 ins. diam., bears S.35*W., 16 lks. dist., mkd. W C $\frac{1}{4}$ S 28 B T
- Desc. 97 ft. along broken NW. slope.
- 60.20 Draw, course N.20*E., asc. 498 ft. over NE. slope.
- 80.08 Cor. of secs. 20, 21, 28 and 29.
- Land; mountainous.
- Soil; rocky, 4th rate.
- Timber; fir, cedar, hemlock, pine, and yew.
- Undergrowth; vinemaple, and arrow-wood.
-
- N.0*03'W., bet. secs. 20 and 21.
- Desc. 128 ft. over NE. slope, through heavy timber and medium undergrowth.
- 5.70 Spur, slopes NE., desc. 533 ft. over NW. slope.
- 16.40 Left bank of North Umpqua River, course SW.,
- 18.70 Right bank of river, asc. 605 ft. over S. slope, over low bluffs and rocks.
- 34.20 Enter cleared land, bears E. and W.,
- 34.63 Intersect line bet. eors. Nos. 3 and 4, H. E. S. No. 178 cor. No. 4 bears N.75*18'W., 176 lks. dist.
- 36.20 Top of asc. bears E. and W., over nearly level land.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 20 and 21, with brass cap marked