


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

- 16.70 Draw, course SW.,
- 19.10 Draw, course SW.,
- 33.50 Spur, slopes SW.,
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 8 and 9, with brass cap mkd.




from which,

A fir, 6 ins. diam., bears S.27*E., 14 lks. dist.,
mkd. $\frac{1}{4}$ S 9 B T

A pine, 8 ins. diam., bears S.34*W., 39 lks. dist.,
mkd. $\frac{1}{4}$ S 8 B T

Asc. 282 ft. over SW. slope.

- 55.60 Spur, slopes SE., desc. 519 ft. over broken NE. slope.
- 68.30 Spur, slopes E.,
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.



from which,

A hemlock, 6 ins. diam., bears N.56*E., 15 lks. dist.,
mkd. T 26 S R 2 E S 4 B T

A fir, 8 ins. diam., bears S.34*E., 13 lks. dist.,
mkd. T 26 S R 2 E S 9 B T

A fir, 5 ins. diam., bears S.19*W., 22 lks. dist.,
mkd. T 26 S R 2 E S 8 B T

A hemlock, 12 ins. diam., bears N.68*W., 47 lks. dist.,
mkd. T 26 S R 2 E S 5 B T

Land; mountainous.