


County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

40.00

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bed rock, and in mound of stone, 2½ ft. base, for ¼ sec. cor. of secs. 31 and 32, with brass cap mkd.



from which,

A pine, 15 ins. diam., bears East, 19 lks. dist.,
mkd. ¼ S 32 B T

A fir, 12 ins. diam., bears S.85*W., 19 lks. dist.,
mkd. ¼ S 31 B T

Desc. 146 ft. over NE. slope.

45.60 Desc. 857 ft. over N. slope.

61.50 Desc. 150 ft. over NE. slope.

65.10 Hole-in-the-Ground Creek, 1 lk. wide, course NW., asc. 91 ft. over broken SW. slope.


68.00 Point of spur, slopes W.,

68.50 Draw, course W.,

71.50 Spur, slopes W., along W. slope.

78.90 Creek, 1 lk. wide, course SW., asc. 102 ft. over SE. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 29, 30, 31 and 32, with brass cap mkd.



from which,

A fir, 14 ins. diam., bears N.41*E., 69 lks. dist.,
mkd. T 26 S R 2 E S 29 B T

A fir, 42 ins. diam., bears S.20*E., 21 lks. dist.,
mkd. T 26 S R 2 E S 32 B T

A fir, 24 ins. diam., bears S.36*W., 143 lks. dist.,