

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 26 S., R. 2 E.

CHAINS

- 73.00 Spur, slopes SW.,
- 77.10 Draw, course SW., asc. 20 ft. over SE. slope.
- 80.08 Cor. of secs. 29, 30, 31 and 32.
Land; mountainous.
Soil; rocky, mountain loam, 4th rate.
Timber; fir, pine, cedar, hemlock, and madrona.
Undergrowth; vinemaple, small fir, arrow-wood, and
rhododendron.
-
- 40.00 S.89*53'W., on a random line bet. secs. 30 and 31.
Set temp. $\frac{1}{4}$ sec. cor.
- 79.42 Intersect W. bdy. of Tp., 9 lks. S. of cor. of secs.
25, 30, 31, and 36, as described in the field notes
of T.26 S., R. 1 E., this Group.
Thence
N.89*57'E., on true line bet. secs. 30 and 31.
Asc. 127 ft. over SW. slope, through heavy timber and
medium undergrowth.
- 2.30 Spur, slopes S., desc. 260 ft. over SE. slope.
- 13.70 Draw, course S., asc. 98 ft. over SW. slope.
- 16.70 Spur, slopes S., desc. 323 ft. over broken SE. slope.
- 39.42 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of secs. 30 and 31, with
brass cap mkd.
- $\frac{1}{4}$ $\frac{830}{331}$
1929
- from which,
A fir, 20 ins. diam., bears N.24*E., 51 lks. dist.,
mkd. $\frac{1}{4}$ S 30 B T
A fir, 20 ins. diam., bears S.54*W., 31 lks. dist.,
mkd. $\frac{1}{4}$ S 31 B T
Desc. 165 ft. over SE. slope.
- 47.30 Creek, 1 lk. wide, course N.75*E., asc. 8 ft. over W.